

INSTRUCTION MANUAL


MICROPHONE

DM-1100


1. GENERAL DESCRIPTION

The TOA DM-1100 is a unidirectional microphone suited for hand-held, general-use applications. This microphone body is rigidly constructed of diecast-aluminum, and designed to reduce switching and handling noises.

2. APPEARANCE



3. CIRCUIT DIAGRAM



4. SPECIFICATIONS

Model	DM-1100
Туре	Moving coil microphone
Directivity	Unidirectional
Rated Impedance	600 Ω, unbalanced
Rated Sensitivity	-55 dB (1 kHz, 0 dB=1 V/Pa)
Frequency Response	100 Hz to 12 kHz
Connection Cable	1-core shielded cable
Cable Length	7.5 m or 24.6 ft
Terminal of Cable	Phone plug
Weight	155 g or 0.34 lb (without connection cable)
Dimensions	ø 55 x 178 mm or ø 2.2 x 7.0 in
Talk Switch	Short-off circuit type, slide switch
Finish	Body: Diecast-alminum, painted Black
	Head: ABS resin, Black / Zinc plated steel wire, painted Black
Standard Accessory	Microphone holder (W5/16", W5/8")

Note: The design and specifications are subject to change without notice for improvement.

URL: http://www.toa.jp/