



Pre-Amplifier

T-2S01



Features

- * 2 channel pre-amplifier with 10 inputs.
- * Remote paging console T-319 mic 1 with highest input priority.
- * Mic 2-4 with VOX selector, priority is over inputs 5-10 and phantom power.
- * All the 10 inputs with mic, line and high pass filtering selector.
- * Inputs 7-10 is optional for XLR mic inputs or dual RCA line inputs.
- * Dual channel XLR line outputs
- * All inputs include inputs 1-10, MIC (remote paging console T-319), chime could be selected to have channel 1, channel 2 and channel 1+2 outputs.
- * Built-in 2/4 tone preset chime, remote chime trigger and local trigger on front panel.
- * Volume controls are provided over chime, MIC1, inputs 2-10, channel 1 and channel 2 Master knob. Bass and treble tone control are provided for both channel 1 and channel 2.
- * Indicator for input 1-10, power and 2 channel.
- * AC 110 or 230V and DC 24V operation.

Specifications

Model	T-2S01
Input Sensitivity/Impedance	
MIC/ Line	-50dBu (2.45mV)/5KΩ balanced, -10dBu (2.45mV)/5KΩ balanced
Line RCA In	-10dBu (2.45mV)/5KΩ unbalanced
Output Level/Impedance	Output Level/Impedance
Master 1, 2	Nor +4dBu/200Ω balanced
REC	Nor 0dBu/10KΩ unbalanced
Frequency Response	-0.5dB(20Hz~20KHz)
S/N Ratio	
MIC	> 60dB
Line	> 75dB
THD	
MIC	< 0.05%
Line	> 0.03%
Cross-talk	>60dB
MIC	
Line	> 75dB
Power Consumption Power	13W
Power Supply	~110V ~230V 50/60Hz & DC 24V
Dimensions	484 x 258 x 44mm
Weight	4.28Kg

Rear Panel

