

Economic Wall Mount IP Active Speaker

T-7707



Description

It is widely applied to classroom, multi-media classroom, office, conference room, prison, hospital office, metro, and other places, to broadcast some recorded audio documents or background music, and to be used as local broadcast.

Features

- * Professional integration wall mounted design, the speaker case designs is conform to sound resonance principle design concept, with excellent appearance.
- * Adopt embedded computer and DSP audio processing technology
- * Build-in one channel network hardware audio decoding module, it supports TCP/IP, UDP, to realize the network transfer audio signal of 16 CD class perfect sound quality.
- * Build-in 2 channel digital amplifier 2 x 20W, 1 channel to connect main speaker, the other connect assistant speaker to fulfill smooth and strong sound quality, with network volume setting.
- * With 1 AUX input, independent volume potentiometer control, support offline local. paging function. Support mute volume preset and background music mix output preset
- *Support 2.4G wireless audio module can be expanded to realize local amplification of the 2.4G wireless microphone.
- *Support connecting with Bluetooth receiver to receive Bluetooth audio for local sound broadcasting.
- * Build-in 2 priority settings:
 - 1) Network voice alarm has higher priority than AUX and Network BGM
 - 2) AUX has higher priority than Network BGM
- * Compatible with Router, PABX, bridge gateway, modem, intelnet, 2G, 3G, 4G, multicast,

unicast and any other network construction.

* Digital products with easy expansion, without geographical restrictions, no need to increase management equipment on the machine room , using a common network from the design concept of line construction for easy installation.

* It supports remote hardware update of the terminal, no need go to upgrade at the local site, to reduce maintenance burdens and make more simple operation.

Specifications

Model	T-7707
Network Interface	standard RJ45 input
Transmission Speed	100Mbps
Protocol Support	TCP/IP,UDP
Audio Format	MP3
Audio Mode	16-bit CD quality
Sampling Rate	8K~48KHz
AUX Input Sensitivity	350mV (unbalanced)
Frequency Response	80Hz~16KHz +1/-3dB
THD	≤1%
SNR	>65dB
Power Consumption	≤50W
Circuit Protection	Overload, short circuit protection
Operating Temperature	5°C~40°C
Operating Humidity	20%~80% relative humidity, non-condensing
Operating Power Supply	~190-240V 50-60Hz
Dimension	190×180×280mm
Net Weight	3Kg

Rear Panel

